

09 10/158245

Patent Claims

1. Method of sending voice messages to telephone subscribers connected via terminals (A, B) to a telecommunications network (N), which in particular is provided with devices for an intelligent network (IN), wherein a caller, after being connected to a server (S), transmits a voice or text message to said server (S), **characterised in that** the caller (A) additionally transmits one or more addressees (B) for said message to said server (S), which subsequently initiates the transmission of said message as voice message to said addressee(s) (B).
2. Method according to Claim 1, characterized in that the caller (A) transmits the desired sending time of the voice message to the server (S).
3. Method according to Claim 1, characterized in that the caller transmits a time window in which the connection attempts are to be made.
4. Method according to Claim 1, characterized in that the addressees are transmitted by inputting the telephone number.
5. Method according to Claim 1, characterized in that the addressees are transmitted by inputting names agreed previously with the service provider for each telephone number.
6. Method according to Claim 1, characterized in that the addressees are transmitted by inputting identifiers previously agreed with the service provider for certain subscriber groups.
7. Method according to Claim 1, characterized in that the message and/or the addressees are transmitted by means

09 10/158245

09/758 24S

of text input.

8. Method according to Claim 1, characterized in that the message and/or addressees are transmitted by means of voice input and a voice recognition is performed in the server (S) to identify the addressees.
9. Method according to Claim 1, characterized in that the inputs of the caller are checked in the server (S) for plausibility and lack of ambiguity and the caller is requested to make a repeat input if necessary.
10. System comprising a telecommunications network (N), one or more servers (S) for receiving and delivering voice messages and terminals (A, B), with means:
 - to receive information of a caller, comprising at least one message and addressees information and
 - to automatically initiate the transmission of said message as voice message to the terminals (B) of said addressees.
11. Server (S), in particular in conjunction with an intelligent network (IN), that is connected to a telecommunications network (N), having:
 - an information storage function (SP) to store information from a caller, comprising at least one message and addressees information,
 - a dialing function (WF) to automatically initiate connections to the addressees (B) and
 - a voice output function (AF) for generating a voice message to be transmitted to addressees.
12. Server (S), according to claim 11, characterized in that the information storage function (SP) is prepared to store voice information from a caller, and that a

09/758 24S

12/1/12

- THE**